Pos.	Masse	Gegenstand	Einheitspreis Euro		Betrag Euro	
1		**DAMTEC® 3D** Profiled underlay for vibration insulation structure borne noise reduction. The best area of use is for loads less than 0.05N/mm². *Manufacturer:* Gummiwerk KRAIBURG RELASTEC GmbH Fuchsbergerstr.4, D-29410 Salzwedel, Tel. +49/8683-701 142, Fax +49/8683-701 4 142 *Material:* High-grade granules of recycled rubber with PU elastomer bonding agent. *Delivery:* rolls Thickness (-1.0mm)/Width (±1.5%)/Length (±1.5%): (8/4)mm/0.8m/15m, (17/9)/0.8/12,5, (23/12)/0.8/12,5 *Physical Characteristics:* tensile strength: approx. 0.3 N/mm² (EN ISO 1798) elongation at break: approx.. 45% (EN ISO 1798) service temperature range: - 40°C to + 80°C flammability rating: E_f (EN 13501-1) max. pressure: 0,05N/mm² resonance frequency at 0,05N/mm², one layer: 8/4 – 30 Hz 17/9 – 20 Hz 23/12 – 17 Hz *Properties:* resistance to moisture absorption and rot degradation, high compressive strength and load-bearing performance *Installation:* In accordance DAMTEC® 3D installation instructions. m² DAMTEC® **vibra 3D**, impact sound insulation				

KRAIBURG Relastec GmbH & Co.KG
Fuchsberger Straße 4 · D-29410 Salzwedel
Tel. +49-(0) 86 83-701-1 42 · Fax +49-(0) 86 83-701-41 42
christina.wallner@kraiburg-relastec.com · www.kraiburg-relastec.com/damtec

Made in Germany
quality austria SYSTEMZERTIFIZIERT ISO 9001:2008 NR.00186/0
CERTIFIED MANAGEMENT SYSTEM IQNet
U.S. GREEN BUILDING COUNCIL MEMBER

Pos.	Masse	Gegenstand	Einheitspreis Euro		Betrag Euro	
1		made of recycled rubber granules, shrank in PE membrane, on pallets to be supplied and installed. Manufacturer: Gummiwerk KRAIBURG RELASTEC GmbH Product: DAMTEC® vibra 3D Thickness: ___ mm; resonance frequency: ___Hz (Interpretation takes place in acc. to requirement profile) Installation has to be in accordance with installation instructions of manufacturer. *(for installation under concrete or screed)* Rolls of duct tape (length: 50m) It is recommended to glue tape over the joints. (in acc. with manufacturer's recommendations). m² PE membrane Thickness: ____ mm After installation of insulating underlay cover it with suitable PE membrane (for example PE 0.2 mm). (in acc. with manufacturer's recommendations). m DAMTEC® vibra 3D, height ____ mm, thickness ____ mm. Decoupling of edges with edge strips (in acc. with manufacturer's recommendations). Materials: _____ Labour: _____				

DISCLAIMER:
Mit unseren Angaben wollen wir Sie aufgrund unserer Versuche und Erfahrungen nach bestem Wissen und Gewissen beraten. Eine Gewährleistung für das Verarbeitungsergebnis kann KRAIBURG RELASTEC im Einzellfall jedoch wegen der Vielzahl an Verwendungsmöglichkeiten und der außerhalb unseres Einflusses liegenden Lagerungs-, Verarbeitungs- und Baustellenbedingungen für seine DAMTEC® Produkte nicht übernehmen. Eigenversuche sind durchzuführen. Unser technischer Kundenservice steht Ihnen gerne zur Verfügung.

Dieser Ausschreibungstext unterliegt keinem Änderungsdienst! Alle Angaben erfolgen ohne Gewähr.
Die jeweils aktuelle, gültige Fassung ist abrufbar unter www.kraiburg-relastec.de/damtec

KRAIBURG Relastec GmbH & Co.KG
Fuchsberger Straße 4 · D-29410 Salzwedel
Tel. +49-(0) 86 83-701-1 42 · Fax +49-(0) 86 83-701-41 42
christina.wallner@kraiburg-relastec.com · www.kraiburg-relastec.com/damtec

Made in Germany
qualityaustria SYSTEMZERTIFIZIERT ISO 9001:2008 NR.00186/0
CERTIFIED IQNet MANAGEMENT SYSTEM
U.S. GREEN BUILDING COUNCIL MEMBER